

### OVERVIEW

The Badger Meter® Model 3700 Data Acquisition Server provides high performance and low cost for:

- Demand response programs.
- Benchmarking building operations performance.
- Verification of energy savings and utility costs.
- Cost allocation to departments or tenants.
- Internet-based supervisory control outputs.

The system combines the flexibility of choosing LAN, modem or cellular communication paths for logging building data such as:

- Industry standard pulse or analog inputs.
- Electrical, gas and water usage and costs.
- Indoor and outdoor temperatures.
- Pressure, humidity and CO<sub>2</sub>.

The Model 3700 brings plug-and-play capability to the data acquisition market, dramatically reducing the time and training required to put a typical building online. In most applications, the installation can be completed by the building engineer or contractor in less than two hours. The system automatically detects and configures Modbus devices in just seconds reducing installation time and costs.

### APPLICATIONS

- Demand response program control and reporting.
- Cost allocation to tenants and third parties.
- Measurement and verification of energy savings.
- Data center branch circuit monitoring.
- Monitoring performance of building systems (for example, chillers, boilers and fans).

### EASY INSTALLATION SAVES TIME AND MONEY

- Simple plug-and-play connectivity to standard Modbus meters minimizes installation time and costs.
- Flex I/O inputs provide easy connections for analog, pulse and resistance sensors.
- Model 3700 hardware and software is designed to provide data in flexible, industry standard formats for databases, spreadsheets and others.
- Model 3700 provides onboard plug in for Data Industrial Model R9120-5 to allow wireless RS-485 communications.
- Integrated relay outputs allow supervisory control from any location for load shedding or local generation.



- Integrated web server provides setup and configuration using any industry standard web browser (such as Netscape or Internet Explorer).

### INTERNET DISPLAY OF KEY BUILDING PARAMETERS

- Buildingmanageronline.com allows authorized users to see building performance data in an easy to use graphical format. Please contact Badger Meter for more information.
- The BMO site provides storage, display and downloads of historical data in a secure SQL database.
- Users can be notified of alarm conditions in any or all monitored points.
- Open protocols provide connectivity to any energy management or building automation software.

### FLEXIBLE COMMUNICATIONS AND WIRELESS CONNECTIVITY

- All data is stored at the site in nonvolatile memory, ensuring protection of valuable information in the event of power loss.
- Optional Model R9120-5 for wireless RS-485 communications.
- Model 3700 provides two communication options: LAN or phone line.

## SPECIFICATIONS

<b>Processor</b>	
<b>Main processor</b>	ARM 9; I/O
<b>Co-processor</b>	ARM 7
<b>Operating System</b>	Linux 2.6
<b>Flash ROM</b>	16 MB NOR Flash (expandable with USB memory device)
<b>Memory</b>	32 MB RAM
<b>LED</b>	8x pulse input, 4 modem activity, Modbus TX/RX, power status
<b>Console</b>	2 x 16 LCD character, two buttons
<b>LAN</b>	10/100, auto crossover detection
<b>Modem (phone)</b>	V.34 bis, 33,600 bps
<b>Protocols</b>	Modbus/RTU, Modbus/TCP, TCP/IP, PPP, HTTP/HTML, FTP, SNMP, SMTP, XML
<b>Power Supply</b>	24V DC, included
<b>Serial Port</b>	RS-485
<b>Approvals</b>	CE, FCC Part 15, Class A
<b>USB Port</b>	USB memory expansion port
<b>Power Requirement</b>	110...120V AC
<b>Interval Recording</b>	User selectable 1...60 minutes. Default 15 minute interval.
<b>Outputs</b>	2x, dry contact 30V DC, 150 mA max
<b>Inputs</b>	8x user selectable
<b>0...10V</b>	Min/max/ave/instantaneous
<b>4...20 mA</b>	Min/max/ave/instantaneous
<b>Pulse</b>	Consumption, rate
<b>Resistance</b>	Min/max/ave/instantaneous
<b>Runtime</b>	Runtime, status

**Control. Manage. Optimize.**

Data Industrial is a registered trademark of Badger Meter, Inc. Other trademarks appearing in this document are the property of their respective entities. Due to continuous research, product improvements and enhancements, Badger Meter reserves the right to change product or system specifications without notice, except to the extent an outstanding contractual obligation exists. © 2016 Badger Meter, Inc. All rights reserved.

**www.badgermeter.com**

The Americas | Badger Meter | 4545 West Brown Deer Rd | PO Box 245036 | Milwaukee, WI 53224-9536 | 800-876-3837 | 414-355-0400  
 México | Badger Meter de las Americas, S.A. de C.V. | Pedro Luis Ogazón N°32 | Esq. Angelina N°24 | Colonia Guadalupe Inn | CP 01050 | México, DF | México | +52-55-5662-0882  
 Europe, Middle East and Africa | Badger Meter Europa GmbH | Nurtlinger Str 76 | 72639 Neuffen | Germany | +49-7025-9208-0  
 Europe, Middle East Branch Office | Badger Meter Europe | PO Box 341442 | Dubai Silicon Oasis, Head Quarter Building, Wing C, Office #C209 | Dubai / UAE | +971-4-371 2503  
 Czech Republic | Badger Meter Czech Republic s.r.o. | Mařikova 2082/26 | 621 00 Brno, Czech Republic | +420-5-41420411  
 Slovakia | Badger Meter Slovakia s.r.o. | Racianska 109/B | 831 02 Bratislava, Slovakia | +421-2-44 63 83 01  
 Asia Pacific | Badger Meter | 80 Marine Parade Rd | 21-06 Parkway Parade | Singapore 449269 | +65-63464836  
 China | Badger Meter | 7-1202 | 99 Hangzhong Road | Minhang District | Shanghai | China 201101 | +86-21-5763 5412